Caractéristiques techniques



Cassette

Model			PCA3U-09HIFNX-QRDOW (GA)
Power supply		V,Hz,Ph	220-240V, 50Hz, 1Ph
Cooling	Capacity	Btu/h	9000
	Input	W	40
	Rated current	A	0,18
Heating	Capacity	Btu/h	10000
	Input	W	40
	Rated current	A	0,18
Indoor fan motor	Model		ZKFP-46-8-1
	Qty		1
	Input	w	46(Output)
	Capacitor	uF	/
	Speed(hi/mi/lo)	r/min	600/520/460
Indoor coil	a.Number of rows		1,0
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1,3
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,inner groove tube
	f.Coil length x height x width	mm	1380x210x13.37
	g.Number of circuits		2
Indoor air flow		m3/h	580/500/450
Indoor sound pressure level		dB(A)	38/33/29
Indoor sound power level		dB(A)	53
Indoor unit	Dimension (W x Dx H) (body)	mm	570x570x260
	Packing (W x Dx H)(body)	mm	655x655x290
	Dimension (W x Dx H)(panel)	mm	647x647x50
	Packing (W x Dx H)(panel)	mm	715x715x123
	Net/Gross weight(body)	kg	14.5/17.3
	Net/Gross weight	kg	2.5/4.5
Design pressure		MPa	4.3/1.7
Drainage water pipe dia.		mm	ODΦ25
Refrigerant piping	Liquid side/ Gas side	mm	Φ6.35/Φ9.52(1/4"/3/8")
Controller			Remote control
Room temperature	Cooling	℃	17-32
	Heating	℃	0-30
Operation temperature		℃	17-30